



JATÃO LINE 3 POINTS



Rua Dr. Luiz Miranda, 1.650 - 17580-000 - Pompeia - SP - Brazil - Tel.: +55 14 3405 2100 - Fax: +55 14 3452 1306 - E-mail: export@jacto.com.br www.jacto.com.br

PROTECT THE ENVIRONMENT. WHEN DISCARDING THIS LEAFLET, DO NOT LITTER THE STREET.



Images are for illustration purposes only and may have different optional accessories and versions. Check available settings at a dealer near you. This leaflet does not void the need to read the operator's manual closely. Jacto may change settings, versions and models offered in this leaflet at any time. 06/2016. 930002162

JATÃO LINE

ROBUSTNESS AND VERSATILITY TO PROTECT YOUR CROP

Jatão Line was designed for farmers who seek efficient application and ensured crop protection, from planting to harvesting.



AJ 401



JATÃO 400



JATÃO 600



SPRAY SYSTEM



AJ 401 / J 400 LONG-RANGE SPRAYING

UPPER DUCT

AJ 401 reaches up to **30** metros,
J 400 reaches up to **35** metros

Providing good coverage in this application range.

Allows low-volume and very-low volume applications.

Very versatile, it can be used in different crops such as **vegetable, flower, grain, fruit crops and livestock.**

Are low-maintenance, light and robust equipment.

LOWER DUCTS

The lower ducts allow spraying near the tractor.
The air duct is easily adjusted horizontally and vertically.



SPRAY SYSTEM

J 600

LONG-RANGE SPRAYING

COMPONENTS. **JATÃO LINE.**

UPPER DUCT

J 600 reaches up to **35** meters

Providing good coverage in this application range.

Allows low-volume and very-low volume applications.

Very versatile, it can be used in different crops such as **vegetable, flower, grain, fruit crops and livestock.**

J 600 is a low-maintenance, light and robust equipment.

LOWER DUCTS

The lower ducts allow spraying near the tractor. The air duct is easily adjusted horizontally and vertically.

FAN

600-mm diameter fan ensures large air volume (9,000 m³/h) providing wider spraying range and perfect deposition.

TANK



400-liter and 600-liter polyethylene tanks and highly resistant to corrosion. Sight glass with graduated scale and mechanical agitation system.

HYDRAULIC ADJUSTMENT



Hydraulic adjustment of the duct allows greater productivity and comfort to the operator (available for J 400 and J 600).

IN-LINE FILTER



On J 400 and J 600, the filtering system of the spraying hydraulic circuit has a FVS-102 suction filter with two stainless steel mesh filtering elements and quick-closing. On AJ 401, the filtering system of the hydraulic circuit has 2 in-line filters, one for each duct.

HYDRAULIC CONTROL



With adjustable position to make the work of the tractor driver easier. Independent lever and quick relief (available for J 400 and J 600).

FILTER



The suction filter retains every type of impurity before it reaches the chemical pump.

CHEMICAL CONTROL UNIT



Allows controlling application volume quickly and efficiently.





SPRAY SYSTEM

TOTAL PROTECTION FOR YOUR CROP





JATÃO LINE



ARBUS AJ 401



JATÃO 400




JATÃO 600



SPRAYING

	AJ 401	JATÃO 400	JATÃO 600
SPRAYING RANGE			
Without wind.....	15 m	20 m	20 m
With 5 km/hour wind.....	25 m	30 m	30 m
with 10 km/hour wind.....	30 m	35 m	35 m
TANK			
Capacity.....	400 Liters	400 Liters	600 Liters
PUMP			
Model.....	Centrifugal (one rotor)	BC 1142 Centrifugal (one rotor)	Centriifugal (two rotor)
Pumping capacity.....	120 L/min	140 L/min	115 L/min
Rotation.....	3628 rpm	3770 rpm	4100 rpm



DIMENSIONS/WEIGHT

	AJ 401	JATÃO 400	JATÃO 600
WEIGHT			
Empty machine.....	230 kg	295 kg	385 kg
DIMENSIONS			
Length.....	1.45m	1.65m	1.25m
Maximum width.....	1.15 m	1.50 m	2.20 m
Height.....	2.00 m	2.25 m	3.85 m